





AGRIMATE

- Unique design consumes less fuel.
- Its unique design allows to work with minimum vibration in the field as well as less operating load on the tractor.
- Rotavator using sealed bearing, providing better protection from dust & Moisture.

AGRIMATE

- Agrimate Rotavator has been designed to work in soft & hard, wet & dry conditions.
- The hellical arrangements of blades allow for better cutting of soil & helping in better pulverisation.
- The working depth is adjustable from the side skid assembly from 3" to 7"
- Multi speed gearbox allows the user to configure the rotavator for optimum operation as per requirements by changing the back gears.





CHAMPION SERIES







FEATURES OF ROTAVATOR

- Heavy duty gear box
- High temp. silicon seals
- All gears EN353 Material
- Side disc is an option attachment
- Unique design consumes less fuel
- Heavy Gear Box in S G IRON 500/7 Grade
- Special High tensile Nut/Bolts 10.9/8.9 Grade
- Hadened Gears for long life and smooth functioning
- Sealed bearings used to protect from dust & moisture
- Adjustable Depth skid to achieve more tiling depth upto 7"
- PTO shaft with shear bolt to avoid overload on Gearbox & Tractor
- Boron steel special blades lasts longer than regular blades. Available in L / J / C type

ROTAVATOR - GEAR TYPE - MULTISPEED-CHAMPION SERIES

MODEL	SIZE	SPEED/RPM	BLADE TYPE	NO. OF BALDES	НР	WEIGHT (aprox)
AM-RT-4030CS	4.0 FEET	540/1000	L Type	30	25-30	370kg
AM-RT-5036CS	5.0 FEET	540/1000	L Type	36	30-35	409kg
AM-RT-5542CS	5.5 FEET	540/1000	L Type	42	35-40	435kg
AM-RT-6042CS	6.0 FEET	540/1000	L Type	42	40-45	451kg
AM-RT-7048CS	7.0 FEET	540/1000	L Type	48	45-50	486kg
AM-RT-8054CS	8.0 FEET	540/1000	L Type	54	60-65	530kg