

# AMTH-V120-60-CLASSIC TEA HARVESTER



**DISCLAIMER:** DUE TO CONSTANT UPGRADATION, FEATURES AND SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE



BEFORE OPERATING THIS MACHINE, PLEASE READ THESE INSTRUCTIONS CAREFULLY





Good Products - Great Values

#### Dear Sir/Madam,

Thank you for choosing Agrimate product. You are the proud owner of high technology and durable machine. Trust that our franchisee/dealer installed the product and explained you about the usage and service instructions. Please visit our authorised dealer for your future requirement of our other equipments, genuine spares, accessories and service. Service coupons are attached with this manual and you can avail free service to keep your machine fit always to use on demand.

#### **About Ratnagiri**

We import and market of high quality of agriculture wide range of equipment's Which we are selling through our authorized franchisee or dealer network. We are in this field from past 20 years serving the former community. For further details, you may please visit our website www.agrimart.in, Tool Free No: 1800-425-3036.

> Range of Brands ▲ Oleo-Mac AGRIMATE **Our Retail Formats** AGRIMARI MEGA

Agriculture | Horticulture | Sericulture | Plantations | Forestry | Garden | Health care

#### **TECHNICAL PARAMETERS**

Product model	AMTH-V120-60-Classic
Engine transmission mode	Automatic centrifugal clutch
Clutch bonding rotating rate	3700-3800
Blade rotating direction	PF-25/ Reciprocating type
Engine model	1E34F
Engine power	0.75
Engine standard rotating rate	7500
Displacement	25.4cc
Method of starting	Recoil starting
Way of ignition	CDI
Fuel model	2-stroke gasoline
Fuel used	Ratio of fuel and lubricant 25-30:1

#### 1. Preface

Thanks for purchasing and utilizing our company's product, and please read the instructions of the product and the engine before operating it so that accidents or injuries can be avoided. After reading, please keep the instructions for whenever you need.

### 2. Safety instruction

- 1. Please accept the safety operation guidance in advance if the users have little knowledge in operating the machine and after that, the machine is available.
- 2. The machine can't be used by the following crowd
- (1)Drunk people (2) Madmen (3) Children and pregnant women
- (4)People who are unable to operate the machine because of overtoil illness and drug allergy
- 3. Operation of clothing
- 1) Long-sleeved clothes and trousers should be worn, but the clothes with wide cuffs should be avoided.

- (2) The cap and the glasses should be worn
- (3) A pair of glove is needed when it is examined and taken good care of
- (4) Slippery shoes should be avoided

### 4. No smoking and open flames

- (1) The placement of the fuel should be valued and the places that are easy to catch fire are avoided
- (2) No smoking when the engine is being operated and the fuel is supplied
- (3) The engine should be stopped when the fuel is supplied. In addition; please dry the fuel on the engine on the occasion that the machine turns upside down or the engine is splashed with the fuel when the fuel is supplied

#### 3. The Connection of the 4C-60 Tea Harvester

- 1.Pull up the pin on the engine output hole, and then put the end of the flexible shaft cover with the hole into the hole.
- Turn around the flexible shaft cover to make the pin insert into the hole, therefore, the fixing of the part of the flexible shaft is finished.
- 3.On the part of the flexible shaft cover with the groove, on one hand, please turn around the square flexible shaft slowly, on the other, push it inwards to make the flexible shaft stick into the square hole of the engine.

- 4. Adjust the flexible shaft and the square hole of the actuating shaft, push the flexible shaft cover with the groove into the flexible shaft setting.
- 5. Stick into the flexible shaft pin and install the cotter pin .Therefore the installation of the flexible shaft is completed.

#### 5. Precautions before operation

- 1.Examination is needed before operation. Please entrust the exclusive shop to fix the machine if it is necessary to adjust the spare parts.
- 2. Objects for examination before operation.

Examination	Content	Approach	
Outlook	Frayed or loose?	Reinforce it	
Fastener	Dropped off or loose?	Fasten it	
Gear case	Grease supplied?	Supply the grease every20-30hrs once	
Blades	Frayed, broken, or deformed/Lubricant?	Change the spare parts/oil	
Air filter	Polluted?	Clarify it	
Fuel tank	Fuel? The fuel tank cover loose?	Oil/fasten it	
Throttle switch	Smooth to operate it from low to high speed?	Adjust/change the spare parts	
Engine switch	ON, OFF works well?	Chang the spare parts	
Blade adjusted nut	The gap of blade well adjusted?	Adjust it	
Handle	Fixed	Adjust it	

### 6. Precautions of Operation

- The fuel must be used with 90# motor petrol and the 2-stroke engine oil, the
  proportion of the petrol and the engine oil must be correct, in the lst 20 hrs,
  the mixing ratio of the petrol and the engine oil is 25:1 and later it will be
  changed int0 30:1.
- 2. No sudden halt of the engine with the high speed operation. The idling speed is adjusted into 2300-2700r/min, no more casual adjustment.
- 3. For per hour of the rotation of the blade, please oil it once with HG-10 motor petrol, and correctly adjust the blade gap.


- 4. Pour the ZFG-10 compound calcium-based grease into the transmission case for every 8-I0 hr operation.
- No severe collision of the machine when moved.
- 6. Tea Harvester can't be used as hedge trimmers.
- 7. Never touch the blade during the operation of the engine, even under the condition of the separation of the clutch.
- Stop the engine when the workplace is changed or the termination of the operation, even under the condition of the short distance.
- 9. Never touch the spark plug during the operation of the engine.
- 10. The curved degree for the flexible shaft of the single tea Harvester should be proper to avoid being broken. Before operation, please wipe the butter of high temperature on the flexible shaft and stick the tube into it and then pull it several times.

## 7. Startup and Halt of the Engine

- Press the oil pump several times before startup, as the fuel goes into the carburetor, then the air could come out, at the same time, please guarantee the close of the throttle control handle.
- 2. As the engine is at the state of cooling or started up in winter, please open the circuit switch and close the choke valve of the carburetor.
- 3. Press the engine and pull the starting rope.
- After starting the engine, the users should accelerate the throttle to make it run idly for 2-3min to keep the engine warm, and then reinforce the throttle to make it work normally.
- 5. **To stop:** Make the throttle switch stay at the low-speed position, reduce the rotating rate of the engine, and keep the cooling operation for 2-3min, then close the circuit switch.

### 8. Reparation and Adjustment of Tea Harvester

- As the blade is the high-speed sliding components, therefore, the lubricant must be poured into once per hour and the blade needs oiling with HG-10 motor petrol.
- 2. Examine and adjust the blade gap. After worked for a certain period, the normal gap of blade will be changed either for the fray of the blade or for the loose of the bolts (about 0.05mm). Therefore, the operation of the blade must be examined, as well as the loose of the bolts and the gap of the blade. The fitness of the blade gap determines the function of plucking and cutting. Overlarge gap will make the blade easy to break,, which will not only have a negative impact on the quality of the tea, but also result in the unevenness of the surface of the tea garden; on the contrary, it is difficult for the operation of the blade with too small gap, or even the blade will be broken easily.



- 1. The upper blade 2.Nut 3. Gasket 4. M6 bolt 5. The nether blade
- 1) Loosen the nut:
- Use the Phillips screwdriver to tighten the screws and then withdraw them for 3/8circle;
- Tighten the nut, at the same time, the blade adjusted gasket should be moved flexibly;
- 4) Oil the blade with lubricant;
- 5) Start the engine to make the blade operate with high speed for 1 min;
- 6) Stop the engine and touch the nut. It works well if the hand bears the tem perature of the nut; if not, loosen the bolt and adjust it to the standard.

#### 9. Questions and Answers

AGRIMATE

#### (1) Unable to start

AGRIMATE

Differences		Reasons	Approaches
No spark during	The spark pl plug	Moistness of the pole	Dry
fire-lighting of		The restoration of carbon of the pole	Clean
the spark plug	Chap of the insulator or low insulation		Change
		Too small/overlarge electrode gap	Adjust 0.5-0.6mm
		The injury of the electrode	Change
	Good compression	Too thick fuel	Adjust the carburetor
		The use of bad fuel	Change the good fuel
Spark during fire-lighting of	Bad compression	Badly worn of the cylinder, piston and piston ring	Change
the spark plug	Carburetor	No fuel	Supply
		Orifice plugging	Eliminate
		The block of the filter network	Clean
	Fuel unsupplied	The loose of the inlet pipe and the carburetor	Fasten

AGRIMATE

AGRIFIATE

AGTIMATE

# (2) Short of power

Differences	Reasons	Approaches	
Good compression no	The air has come into the seam of the inlet pipe	Fasten	
burning flameout	The air has come into the inlet pipe and carburetor	Airproof and fasten	
	The fuel is mixed with water Change the high-quali fuel		
	The piston has a burning smell	Clean every spare parts	
	Carbon piled around	Clean	
Overheat	Too thin fuel	Adjust the carburetor	
	Dust piled on the fan cover and cylinder cooling pin	Eliminate	
Vibration	Low-quality fuel	Change high-quality fuel	
noise(abnormal)	Carbon piled in the fuel cell	Clean	
Others	The block of the air filter	Clean	
	Overload	Proper load	

## (3) Halt of the Operation

AGRIMATE

Differences	nces Reasons Approaches		
EL CALLE CONTRACTOR CO		Revise the piston and cylinder with file/change the sintering ring	
operation	Short circuit for the piling of the carbon	Clean the carbon	
	Problems is the magneto	Examine	
	Breakdown of the spark plug cap	Embed as the original form	
	Scarce fuel	Fill	
Halt for the low rotating rate	The block of the interior carburetor	Examine and clean	
	The fuel is mixed with water	Fulfill the fuel again	

AGRIMATE

AGRIMATE

AGRIMATE

AGRIMATE

### (4) Halt Difficulty


Differences	Reasons	Approaches	
Carburetor	Overheat of the piston and spontaneous combustion inside		
Others	Red and hot of the top of the spark plug	e Eliminate the electrode and adjust the gap(0.5-0.6mm)	
	Cable loss	Insert into	

# 10. Appendix

# (1) 1Engine Data

Engine model	1E34F	1
Displacement	25.4CC	/
Max.power	0.75KW/7500rpm	/
Fuel tank capacity	0.6L	/
Ratio of fuel and	The 1st 20hours	25:1
lubricant	20hours later	30:1

# PART DIAGRAM OF AMTH-V120-60-CLASSIC TEA HARVESTER



SI. No.	Part No.	Description	
1	AMTH-V120-60 CL01	Screw	
2	AMTH-V120-60 CL02	inlet wind net	
3	AMTH-V120-60 CL03	Screw	
4	AMTH-V120-60 CL04	Fan cover(Upper)	
5	AMTH-V120-60 CL05	Fan	
6	AMTH-V120-60 CL06	Fan cover Lower pressing plate	
7	AMTH-V120-60 CL07	Fan cover (Lower)	
8	AMTH-V120-60 CL08	Nut	
9	AMTH-V120-60 CL09	Fan seat	
10	AMTH-V120-60 CL10	Square shaft joint	
11	AMTH-V120-60 CL11	Spacer	
12	AMTH-V120-60 CL12	Drive Bevel Gear	
13	AMTH-V120-60 CL13	Nut	
14	AMTH-V120-60 CL14	Rotatory seat	
15	AMTH-V120-60 CL15	Bearing	
16	AMTH-V120-60 CL16	driven bevel Gear	
17	AMTH-V120-60 CL17	Gearbox	
18	AMTH-V120-60 CL18	Bearing	
19	AMTH-V120-60 CL19	Lower gear shaft	
20	AMTH-V120-60 CL20	Left hand grip	
21	AMTH-V120-60 CL21	Butterfly screw	
22	AMTH-V120-60 CL22	Throttle cable	
23	AMTH-V120-60 CL23	Accelator Switch	
24	AMTH-V120-60 CL24	Stop switch cable	
25	AMTH-V120-60 CL25	Left Handle Seat	
26	AMTH-V120-60 CL26	Handle pressure plate	

SI. No.	Part No.	Description	
27	AMTH-V120-60 CL27	Screw	
28	AMTH-V120-60 CL28	screw	
29	AMTH-V120-60 CL29	Gear case cover	
30	AMTH-V120-60 CL30	Bearing	
31	AMTH-V120-60 CL31	Bearing	
32	AMTH-V120-60 CL32	Anti friction plate	
33	AMTH-V120-60 CL33	Connecting rod	
34	AMTH-V120-60 CL34	Bearing	
35	AMTH-V120-60 CL35	Big gear	
36	AMTH-V120-60 CL36	Screw	
37	AMTH-V120-60 CL37	Wool Felt	
38	AMTH-V120-60 CL38	Balde fixture Block	
39	AMTH-V120-60 CL39	Screw	
40	AMTH-V120-60 CL40	screw	
41	AMTH-V120-60 CL41	Fan Axis	
42	AMTH-V120-60 CL42	Screw	
43	AMTH-V120-60 CL43	Bearing	
44	AMTH-V120-60 CL44	Bearing	
45	AMTH-V120-60 CL45	Bearing	
46	AMTH-V120-60 CL46	Screw	
47	AMTH-V120-60 CL47	Mangenese Steel gasket	
48	AMTH-V120-60 CL48	Balde Screw	
49	AMTH-V120-60 CL49	Balde	
50	AMTH-V120-60 CL50	Tea bag hook	
51	AMTH-V120-60 CL51	Clutch seat	
52	AMTH-V120-60 CL52	Right handle	

SI. No.	Part No.	Description	
53	AMTH-V120-60 CL53	Right handle cover	
54	AMTH-V120-60 CL54	Screw	
55	AMTH-V120-60 CL55	Nut	
56	AMTH-V120-60 CL56	Blade cover	
57	AMTH-V120-60 CL57	Fixed Bayonet lock	
58	AMTH-V120-60 CL58	Balde Screw	
59	AMTH-V120-60 CL59	Drive soft shaft	
60	AMTH-V120-60 CL60	Drive soft Hose	
61	AMTH-V120-60 CL61	Screw	
62	AMTH-V120-60 CL62	Bearing	
63	AMTH-V120-60 CL63	Circlip	
64	AMTH-V120-60 CL64	Clutch disc	
65	AMTH-V120-60 CL65	Screw	
66	AMTH-V120-60 CL66	Screw	
67	AMTH-V120-60 CL67	Self locking nut	
68	AMTH-V120-60 CL68	Collecting plate	
69	AMTH-V120-60 CL69	Blade press Plate	
70	AMTH-V120-60 CL70	Self locking nut	
71	AMTH-V120-60 CL71	Slider	
72	AMTH-V120-60 CL72	Screw	
73	AMTH-V120-60 CL73	Blade support -Right	
74	AMTH-V120-60 CL74	Slide Support plate-right	
75	AMTH-V120-60 CL75	Screw	
76	AMTH-V120-60 CL76	Self locking nut	
77	AMTH-V120-60 CL77	Bag hook	
78	AMTH-V120-60 CL78	Self tapping screw	


AGRIMATE

AURIMATE

AGRIFIATE

SI. No.	Part No.	Description	
79	AMTH-V120-60 CL79	Wind pipe End cap	
80	AMTH-V120-60 CL80	Wind pipe	
81	AMTH-V120-60 CL81	Screw	
82	AMTH-V120-60 CL82	Backpack Frame	
83	AMTH-V120-60 CL83	Screw	
84	AMTH-V120-60 CL84	Back Cushion	
85	AMTH-V120-60 CL85	Straps	
86	AMTH-V120-60 CL86	Damping Spring	
87	AMTH-V120-60 CL87	Nut	
88	AMTH-V120-60 CL88	Flat gasket	
89	AMTH-V120-60 CL89	Triangle plate	
90	AMTH-V120-60 CL90	Screw	
91	AMTH-V120-60 CL91	Bearing	
92	AMTH-V120-60 CL92	Screw	
93	AMTH-V120-60 CL93	Engine bracket	
94	AMTH-V120-60 CL94	Screw	
95	AMTH-V120-60 CL95	Screw	

AGRIMATE



LIMITED WARRANTY PERIOD: For a period of six months from the date of Sale / delivery of the product which ever is earlier. 2. LIMITED
WARRANTY OBLIGATION: Replacement of defective part(s) by authorized dealer are free of charges. If found defective by reasons of defective
material / poor workmanship, parts will be replaced and there will be no value re-imbursement. 3. TERMS & CONDITIONS: a. Claims under
warranty will be accepted on submission of Warranty Card duly filled and stamped by authorized dealer together with the original purchase
document.: b. Shipping / transportation / Incidental charges incurred in replacing defective parts under warranty shall be borne by the purchaser.

#### WARRANTY null & void if

- (ii) Lack of maintenance, (ii) Incorrect use of the machine or tampering, (iii) Use of non-genuine spare parts, (iv) Usage of acids, solvents, or any flammable materials, (v) Non-usage of filter water/ clear water/ soft water & using water above 40°C temperature, (vi) While using the pressure washers to draw water which is contaminated with dust & solvents (eg. paint thinners, gasoline, oil, etc.), (vii) Repair done by unauthorized service people, (viii) Those parts subject to wear & tear due to normal operations and plastic parts, rubber items etc., (ix) Loose connections, faulty electrical fixtures & fluctuations in power supply.
- Should any failure occur during or after the warranty period, customer does not have the right to interrupt payment / price discount.
- 5. Incidental or consequential damages like inconvenience commercial loss, loss of tie, mental agony etc.
- Loss of any nature due to operation or non-operation is not covered under warranty.
- 7. All free service are at Dealer's service point only.
- Warranty ceases if service is not done periodically.
- 9. The attached card should be completed and returned to Ratnagiri Impex Pvt. Ltd. for registration immediately after sale / delivery.
- 10. The warranty is void unless you register the warranty card with Ratnagiri Impex Pvt. Ltd.
- 11. The decision of Ratnagiri Impex Pvt. Ltd., in settling the warranty is final in all respects.
- 12. All disputes are subject to Bangalore Courts Jurisdiction
- LIMITED WARRANTY PERIOD: For a period of six months from the date of Sale / delivery of the product which ever is earlier. 2. LIMITED
  WARRANTY OBLIGATION: Replacement of defective part(s) by authorized dealer are free of charges. If found defective by reasons of defective
  material / poor workmanship, parts will be replaced and there will be no value re-imbursement. 3. TERMS & CONDITIONS: a. Claims under
  warranty will be accepted on submission of Warranty Card duly filled and stamped by authorized dealer together with the original purchase
  document.: b. Shipping / transportation / Incidental charges incurred in replacing defective parts under warranty shall be borne by the purchaser.

#### WARRANTY null & void if

- (ii) Lack of maintenance, (iii) Incorrect use of the machine or tampering, (iii) Use of non-genuine spare parts, (iiv) Usage of acids, solvents, or any flammable materials, (v) Non-usage of filter water / clear water / soft water & using water above 40°C temperature, (vi) While using the pressure washers to draw water which is contaminated with dust & solvents (eg. paint thinners, gasoline, oil, etc.), (viii) Repair done by unauthorized service people, (viii) Those parts subject to wear & tear due to normal operations and plastic parts, rubber items etc., (ix)Loose connections, faulty electrical fixtures & fluctuations in power supply.
- Should any failure occur during or after the warranty period, customer does not have the right to interrupt payment / price discount.
- 5. Incidental or consequential damages like inconvenience commercial loss, loss of tie, mental agony etc.
- 6. Loss of any nature due to operation or non-operation is not covered under warranty.
- 7. All free service are at Dealer's service point only.
- 8. Warranty ceases if service is not done periodically.
- 9. The attached card should be completed and returned to Ratnagiri Impex Pvt. Ltd. for registration immediately after sale / delivery.
- 10. The warranty is void unless you register the warranty card with Ratnagiri Impex Pvt. Ltd.
- 11. The decision of Ratnagiri Impex Pvt. Ltd., in settling the warranty is final in all respects.
- 12. All disputes are subject to Bangalore Courts Jurisdiction
- 1. LIMITED WARRANTY PERIOD: For a period of six months from the date of Sale / delivery of the product which ever is earlier. 2. LIMITED WARRANTY OBLIGATION: Replacement of defective part(s) by authorized dealer are free of charges. If found defective by reasons of defective material / poer workmanship, parts will be replaced and there will be no value re-imbursement. 3. TERMS & CONDITIONS: a. Claims under warranty will be accepted on submission of Warranty Card duly filled and stamped by authorized dealer together with the original purchase document.: b. Shipping / transportation / Incidental charges incurred in replacing defective parts under warranty shall be borne by the purchaser.

#### WARRANTY null & void if

- (ii) Lack of maintenance, (ii) Incorrect use of the machine or tampering, (iii) Use of non-genuine spare parts, (iv) Usage of acids, solvents, or any flammable materials, (v) Non-usage of filter water/clear water/s off water 8 using water above 40°C temperature, (vi) While using the pressure washers to draw water which is contaminated with dust & solvents (eg. paint thinners, gasoline, oil, etc.), (vii) Repair done by unauthorized service people, (viii) Those parts subject to wear & tear due to normal operations and plastic parts, rubber items etc., (ix) Loose connections, faulty electrical fixtures & fluctuations in power supply.
- 4. Should any failure occur during or after the warranty period, customer does not have the right to interrupt payment / price discount.
- Incidental or consequential damages like inconvenience commercial loss, loss of tie, mental agony etc.
- 6. Loss of any nature due to operation or non-operation is not covered under warranty.
- 7. All free service are at Dealer's service point only.
- 8. Warranty ceases if service is not done periodically.
- 9. The attached card should be completed and returned to Ratnagiri Impex Pvt. Ltd. for registration immediately after sale / delivery.
- 10. The warranty is void unless you register the warranty card with Ratnagiri Impex Pvt. Ltd.
- 11. The decision of Ratnagiri Impex Pvt. Ltd., in settling the warranty is final in all respects.
- 12. All disputes are subject to Bangalore Courts Jurisdiction



AGRIMATE

AGRIFIATE

AGRIMATE

#### 1st Free Service Coupon

AGRIMATE

AGRIFIATE

	ratnagin impex	s dervice doupon	ISO 9001 2015 CERTIFIED COMPANY
STREET STREET	FREE SERVICE COUPON (30	Days / 30 hrs (Which ever is earlier)	1 - Vi. 302 - H. SWEN - 1903 - 1904
	Model	Serial Number	7
	AMTH-V120-60-CLASSIC TEA HARVESTER	10	WARRANTY AND FREE SERVICE COUPON
	DDLD	D. I	5
	PDI Date	Purchase bill no. Date	8
			- 5
	Service No.		<b>7</b> ∧ ≅
		Operations:	S
		<ul> <li>Check and Test the Fuel Mixture.</li> <li>Oheck and Clean the Air Filter</li> </ul>	MA HA
		<ul> <li>Check, Clean and Adjust the Spark plug</li> </ul>	
	Dealer's Office Seal	<ul> <li>Check and Adjust the Carburstor Tuning</li> </ul>	
		<ul> <li>Check and Sharpen the cutting Tools</li> <li>Start and Check the Noise, Vibration, Loo</li> </ul>	sen / Fasteners etc.
		<ul> <li>Product familiarization on Usage</li> </ul>	4 ≥
		<ul> <li>Routine maintenance and Storage</li> </ul>	AN
	Dealer Signature	Customer Signature	25
	Conditions: Operations listed have been performed to my e	Customer Signature	W
estro Verv	continues operanius nates nates deen performed in my er		names were charged.
	ASSINATE agriculture I hortical	Iture I sericulture I plantations I forestry I garden I healt	h care
	Max.		
	ratnagin 2nd Fre	e Service Coupon	ISO 9001 2015
	ratnagin		CERTIFIED COMPANY
12	FREE SERVICE COUPON (60	Days / 60 hrs (Which ever is earlier)	
GR	Model	Serial Number	
	AMTH-V120-60-CLASSIC TEA HARVESTER		) S
			WARRANTY AND FREE SERVICE COUPON
	PDI Date	Purchase bill no. Date	
			8
	Service No.		2
		Operations.  • Check and Test the Fuel Mixture.	S
		Oheck and Clean the Air Filter	出
		Check, Clean and Adjust the Spark plug	딾
	Dealer's Office Seal	Oheck and Adjust the Carburetor Tuning     Check and Sharpen the cutting Tools	9
		<ul> <li>Start and Check the Noise, Vibration, Loo</li> </ul>	sen / Fastenors etc.
		<ul> <li>Product familiarization on Usage</li> </ul>	È
		<ul> <li>Routine maintenance and Storage</li> </ul>	A
	Dealer Signature	Customer Signature	50
	Conditions: Operations listed have been performed to my el		mables were charried.
ld			5-251-0-15-0-15-0-15-0-15-0-15-0-15-0-15
GFI	AGRIPATE agriculture I hortica	thure I sericulture I plantations I forestry I garden I healt	n care
	3rd Free	e Service Coupon	
	ratnagin	s octation deapon	ISO 9001-2015
GF.	THE COME STATE OF THE PARTY OF		CERTIFIED COMPANY
opano Pari		Days /120hrs (Which ever is earlier)	
	Model	Serial Number	2
	AMTH-V120-60-CLASSIC TEA HARVESTE		0
	PDI Date	Purchase bill no. Date	8
			0
	Coming No.		ANTY AND FREE SERVICE COUPON
	Service No.	Operations:	Ē.
	——————————————————————————————————————	Check and Test the Fuel Mixture.	S
		<ul> <li>Oheck and Clean the Air Filter</li> </ul>	L.
	Y CU	<ul> <li>Check, Clean and Adjust the Spark plug</li> <li>Oheck and Adjust the Carburetor Tuning</li> </ul>	DG.
	Dealer's Office Seal	<ul> <li>Check and Sharpen the cutting Tools</li> </ul>	물
		<ul> <li>Start and Check the Noise, Vibration, Loo</li> </ul>	sen / Fasteners etc.
		<ul> <li>Product familiarization on Usage</li> <li>Routine maintenance and Storage</li> </ul>	E
		- notine mannenence and othrage	¥

Conditions: Operations listed have been performed to my entire satisfaction without any labour charges. Only consumables were charged.

Customer Signature..

Dealer Signature.

AGRIMATE

AGRIMATE



- Always read the instruction manual supplied along with the equipments and understand the correct installation and operating procedures before attempting to use the equipments.
- It is important to use the personal protection equipments such as head helmet with visor, ear defenders, goggles, safety gloves, cut resistant shoes, trousers and jackets while operating potentially dangerous machines.
- Avoid untrained persons using the equipments. Children must not be allowed to handle these
  equipments.
- Always use genuine spares and accessories in repairs and usage to derive maximum life of the equipments.
- Always keep the equipments in good working condition to minimize loss of output as well as to reduce the pollution and save the environment.
- Do not use the machine within range of persons unless they wear protective clothing.
- Do not operate the machine when fatigued or under the influence of alcohol or drugs.
- For more guery kindly contact for our Service Center/Dealer/ franchise







Small and Timely Maintenance - Big Savings

# **MULTIPLY PROFITS**

# WITH OUR MULTI CROP, MULTI PURPOSE EQUIPMENTS







SPRAYER

PORTABLE MANUAL **POWER** 



KNAPSACK **POWER SPRAYER** 



TILLER



CHAFF CUTTER



**PRUNER** 



**FOGGER** 



**POWER** CHAINSAW

ROTARY LAWN TILLER MOWER



HIGH PRESSURE WASHER



SPRAYER

**EARTH AUGER** 



▲ Oleo-Mac **RANGE OF** 

**PRODUCTS** 



WEEDER

**RANGE OF PRODUCTS** 



**BRUSH CUTTER** - PUSH TYPE



BRUSH CUTTER -**BACK PACK** 



**BRUSH CUTTER -**MULTI TOOL



POLE PRUNER



**BLOWER BACK PACK** 



BRUSH **BACK PACK** CUTTER











OUR RETAIL FORMATS







IMPORTERS & MARKETED BY:

Ratnagiri Impex Pvt. Ltd.

Annapurna House, # 1/1G, 7th Cross New Guddadahalli, Mysore Road Bangalore - 560 026, India Ph: 080-26985100/1/2 Email: info@ratnagiriimpex.com



www.ratnagiriimpex.com





An ISO 9001:2015 Certified Company