

Lawn Mower

Ultimate 20



GXV 160



TRANSMISSION SPECIFICATION

Area	To cover an area of 2400m ²
Type	Self Propelled Type
Cutting Width	20"/508mm
Grass Discharge	Rear Collection
Grass Bag	PVC Hard Case Box 70
LDrive Speed (Min - Max)	0 - 3.96 kmph
Deck	MS/Alloy Body
Net/Gross Weight	40kgs/42kgs
Wheels	8" Front & 7.5" Rear X 45mm Tyre Width With Ball Bearing
Cutting Height	15mm-75mm - 10 Stage Cutting Height - Single Lever Sysytem
Grass Cutting Blade	Disc Type - Swing Back- 4 Blade System
Safety	Brake Lever For Immediate Stop

ENGINE SPECIFICATION

Engine	GXV 160 Air-cooled 4 Stroke OHV Gasoline Engine
Bore x Stroke	68 X 45 mm
Displacement	163 cm3
Net Power Output*	4.3 HP (3.2 kW) @ 3,600 rpm
Net Torque	7.1 lb-ft (9.6 Nm) @ 2,500 rpm
PTO Shaft Rotation	Counterclockwise (from PTO shaft side)
Compression Ratio	8.0:1
Carburetor	Float Type
Ignition System	Transistorized magneto
Starting System	Recoil
Lubrication System	Splash
Governor System	Centrifugal Mechanical
Air cleaner	Dual element
Oil Capacity	0.69 US qt (0.65l)
Fuel Tank Capacity	1.5 U.S. qts (1.4 liters)
Fuel	Unleaded 86 octane or higher
Dry Weight	32 lb (14.5 kg)

Features: • OHV fuel efficient Engine • Easy start • 10 Stage cutting height - single lever system • Disc with 4 swing back blade system • Safety brake system • Rear discharge • 70 litre big grass catcher • Steel Deck • Suitable for Indian & Mexican Lawn



Ratnagiri Impex Pvt. Ltd.,

Annapurna House, # 1/1G, 7th Cross, New Guddadahalli,

Mysore Road, Bangalore -560 026, INDIA

Ph: 080-26985100/1/2. Fax: 080-26751658

Email: marketing@ratnagiriimpex.com | www.ratnagiriimpex.com



Marketed by
ratnagiri impex
BRINGING YOU THE FUTURE... NOW