

CHAINSAW



For Trade Enquiries:
86181 50908 | 86181 58126

Ratnagiri Impex Pvt. Ltd.
Annapurna House, 1/1G, 7th Cross, Mysore Rd, New Guddadahalli, Bengaluru, Karnataka 560026
Web: www.myoleo-mac.com, **Email:** customersupport@ratnagiriimpex.com

Agriculture | Horticulture | Sericulture | Plantations | Forestry | Garden | Health Care



The EasyLift oil and mixture caps are the most practical solution for fast fluid top-up. The conveniently folding rear handgrip is ergonomic and ensures easy use of the filler caps without the need for tools.



Nylon filter: the large filtration surface increases working time between filter cleaning operations.



Decompression valve: facilitates engine starting without kick-back, reducing operator effort.



OnBoard clutch: quick fitting of bar and chain, cleaner clutch for lasting performance.



GS 650 CHAINSAW

Power/Displacement	4.7 HP – 3.5 kW/63.4 cm ³
Bar length (nose)	46-51 cm /18"-20" (replaceable sprocket) 51-61-71 cm /20"-24"-28" (stellite)
Chain (pitch x gauge)	3/8" x .058"
Oil pump	automatic/adjustable/zero flow rate at idle speed
Oil/fuel tank capacity	0.45 L/0.80 L
Sound pressure/power level	103.3/112 dB(A)
Lh/rh vibration level	5.3/5.3 m/s ²
Dry weight without bar and chain	6.5 kg

