

# TELESCOPIC PRUNER



For Trade Enquiries:  
**86181 50908 | 86181 58126**

**Ratnagiri Impex Pvt. Ltd.**  
Annapurna House, 1/1G, 7th Cross, Mysore Rd, New Guddadahalli, Bengaluru, Karnataka 560026  
Web: [www.myoleo-mac.com](http://www.myoleo-mac.com), Email: [customersupport@ratnagiriimpex.com](mailto:customersupport@ratnagiriimpex.com)

Agriculture | Horticulture | Sericulture | Plantations | Forestry | Garden | Health Care



# TELESCOPIC PRUNER



Piston with 2 rings, nickel-plated diecast cylinder, forged connecting rod and crankshaft: all features guaranteed to make the engine extremely rugged and durable.



Straightforward pruner fixing system: with 5 alternative cutting positions (from 0° to 90°) for maximum visibility of the operating area and greater precision (**PPX 271**).



AlwaysOn switch: rapid engine stopping and, thanks to the autoreset function, always ready to restart.



Aluminium clutch housing and cover: optimised and reduced weight of the machine while imparting high strength and lasting reliability.



## PPX 270

## TELESCOPIC POLE PRUNER

Power/Displacement	1.3 HP – 1.0 kW/27.0 cm <sup>3</sup>
Adjustment of pruning head	From 0° to 90° (5 positions)
Bar length (nose)	25 cm/10" (microlite sprocket)
Chain (pitch x gauge)	3/8" x .043"
Overall length of machine	2.60 m / 3.80 m
Dry weight of complete tool without bar and chain	7.4 kg

